

# COMPRESSORS UNLIMITED INTERNATIONAL, LLC

2531 South Beltline Road • Dallas, TX 75253  
 972-286-2264 • 1-800-789-9890 • 972-286-5545 fax  
 sales@cuillc.com

|              |          |          |          |          |          |          |          |
|--------------|----------|----------|----------|----------|----------|----------|----------|
| <b>MODEL</b> | <b>2</b> | <b>F</b> | <b>5</b> | <b>B</b> | <b>8</b> | <b>8</b> | <b>N</b> |
| <b>DIGIT</b> | <b>1</b> | <b>2</b> | <b>3</b> | <b>4</b> | <b>5</b> | <b>6</b> | <b>7</b> |

**REFRIGERANT TYPE**  
 1 = R12 (HERMETIC ONLY)  
 2 = R22 (HERMETIC ONLY)  
 3 = OPEN DRIVE

| MODEL (TONS) |      |      |      |      |
|--------------|------|------|------|------|
| CYL..        | E    |      | F    |      |
|              | R-12 | R-22 | R-12 | R-22 |
| 3            | -    | -    | 10   | 15   |
| 4            | 30   | 50   | 12.5 | 20   |
| 5            | 40   | 60   | 15   | 25   |
| 6            | 50   | 75   | 20   | 30   |
| 8            | 60   | 100  | 25   | 40   |

**SPEED 5 = 1800 RPM**

|          |   |
|----------|---|
| <b>N</b> | <b>SOLENOID UNLOADING</b>                 |
| <b>W</b> | <b>100% UNLOADING (100% UNLOAD START)</b> |
| <b>R</b> | <b>RIGHT HAND</b>                         |
| <b>L</b> | <b>LOW LIFT VALVES</b>                    |
| <b>Z</b> | <b>REMOTE MOUNT ELECT. SOL. UNLOAD</b>    |
| <b>Y</b> | <b>100% UNLOAD w/ REMOTE SOLENOID</b>     |
| <b>X</b> | <b>NON UNLOADING COMPRESSOR</b>           |

| ELECTRICAL CHARACTERISTICS |                                    |
|----------------------------|------------------------------------|
| <b>0</b>                   | <b>OPEN</b>                        |
| <b>1</b>                   | <b>460-3-60 SIX LEAD</b>           |
| <b>2</b>                   | <b>575-3-60 SIX LEAD</b>           |
| <b>7</b>                   | <b>440-3-60 SIX LEAD</b>           |
| <b>8</b>                   | <b>200/230/460/-3-60 NINE LEAD</b> |
| <b>9</b>                   | <b>480-3-60 SIX LEAD</b>           |

**NUMBER OF CYLINDERS 3, 4, 5, 6 OR 8**

**DESIGN SEQUENCE A, B, C, D**